

View Online at <https://aerobasegroup.com/nsn/5305-01-627-2954>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.531 inches

Fastener Length:

1.219 inches

Head Style:

Flat chamfer

Head Diameter:

0.429 inches

Head Height:

0.071 inches

Hole Diameter:

Between 0.076 inches and 0.081 inches

Grip Diameter:

Between 0.3110 inches and 0.3120 inches

Point Length:

0.052 inches

Shank Unthreaded Hole Diameter:

0.076 inches and 0.081 inches threads

Point Style:

Flat

Internal Drive Style:

High-torque

End Application:

F-15sa

Thread Diameter:

0.3125 inches

Grip Length:

0.688 inches

Hole Quantity:

1

Hole Type:

Drilled

Features Provided:

Cetyl alcohol lubricant

Thready Qty Per Inch (tpi):

24

Hole Configuration Style:

Round

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.095 inches and 1.105 inches threads

Point Chamfer Angle:

45.0 degrees

Product Name:

Screw-close tolerance, 100 degrees c'sunk, hi-torque, reduced head

Material:

Nickel alloy 718

Surface Treatment:

Aluminum

Surface Treatment Specification:

Mil-c-83488 type ii class 3 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.