## NSN 5305-01-628-1658



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-628-1658 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.255 inches and 0.285 inches **Fastener Length:** Between 0.695 inches and 0.725 inches **Head Style:** Flat countersunk **Head Diameter:** 0.223 inches **Shoulder Diameter:** 0.141 inches and 0.142 inches first shoulder **Shoulder Length:** 

0.480 inches first shoulder

**Internal Drive Style:** 

Slot

**Thread Diameter:** 

0.138 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

150000 pounds per square inch

Hardness Rating:

33.0 rockwell c and 37.0 rockwell b

**Countersink Angle:** 

100.0 degrees

**Shoulder Shape:** 

Round first shoulder

Color:

Red top of head

Material:

Steel comp 4037 or steel comp 8740

**Surface Treatment:** 

Cadmium and chromate

**Surface Treatment Specification:** 

Qq-p-416, type 2, cl2 federal specification single treatment response

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

## NSN 5305-01-628-1658

Shoulder Screw - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0