NSN 5305-01-628-4510

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-628-4510 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.578 inches **Fastener Length:** Between 1.4235 inches and 1.4535 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.5504 inches and 0.5604 inches **Head Height:** 0.077 inches **Spline Major Diameter:** Between 0.154 inches and 0.156 inches **Grip Diameter:** Between 0.3740 inches and 0.3745 inches **Point Style:** Flat **Internal Drive Style:** Torx **Grip Length:** 0.9375 inches **Nonstandard Thread Pitch Diameter:** -0.2175 to 0.2175 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Point Chamfer Angle:** 45.0 degrees **Product Name:** Bolt, 100 degree reduced head, gear drive recess - 6al-4v titanium (95 kksi shear) Material: Titanium **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5305-01-628-4510

Close Tolerance Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0