## NSN 5305-01-628-7407

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-628-7407 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.403 inches **Fastener Length:** 0.9655 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.3504 inches and 0.3988 inches **Grip Diameter:** Between 0.2641 inches and 0.2651 inches **Internal Drive Style:** Offset cruciform (torque set) **End Application:** F16 **Thread Diameter:** 0.25 inches **Grip Length:** 0.5625 inches Thready Qty Per Inch (tpi): 28 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Bolt, shear, 100 degrees flush reduced head, offset cruciform, 95 ksi fsu. **Special Features:** Max two incomplete threads. Heat treat to 160-180ksi ftu. Replacement oversized repair bolt. Grip is 0.156 versized. Diameter is 0.2646 min to 0.2651 max. Steel comp 4140 or steel comp 4340 or steel comp 8740 **Surface Treatment:** Cadmium **Thread Series Designator:** Unjf Shelf Life:

Demilitarization: No

**Unit Of Measure:** 

N/a

## NSN 5305-01-628-7407

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0