## NSN 5305-01-629-1661

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-629-1661 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.604 inches **Fastener Length:** Between 0.720 inches and 0.750 inches **Head Style:** Flat fillister First Diameter From Head: 0.164 inches **Second Diameter From Head:** Between 0.116 inches and 0.118 inches **Third Diameter From Head:** 0.164 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.411 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.557 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: Between 0.720 inches and 0.750 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.164 inches Width Across Flats: 0.143 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity: Product Name:** Captive screw, damper Material: Stainless steel **Surface Treatment: Passivate Thread Series Designator:** Unrc Shelf Life:

N/a

## NSN 5305-01-629-1661

Externally Relieved Body Screw - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0