

View Online at <https://aerobasegroup.com/nsn/5305-01-629-1661>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.604 inches

**Fastener Length:**

Between 0.720 inches and 0.750 inches

**Head Style:**

Flat fillister

**First Diameter From Head:**

0.164 inches

**Second Diameter From Head:**

Between 0.116 inches and 0.118 inches

**Third Diameter From Head:**

0.164 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.411 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

0.557 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

Between 0.720 inches and 0.750 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.164 inches

**Width Across Flats:**

0.143 inches

**Thready Qty Per Inch (tpi):**

32

**Externally Relieved Body Diameter Quantity:**

1

**Product Name:**

Captive screw, damper

**Material:**

Stainless steel

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unrc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0