NSN 5305-01-629-9816

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-629-9816 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.594 inches **Fastener Length:** Between 1.498 inches and 1.528 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.5149 inches and 0.5662 inches **Head Height:** 0.081 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **Internal Drive Style:** Torque-set ribbed **Thread Diameter:** 0.375 inches **Grip Length:** Between 0.990 inches and 1.010 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 7200 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Stainless steel **Material Specification:** A-286 ams 5731, 5732, 5737, , 5853 assn standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 military specification all treatment responses **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-629-9816

Close Tolerance Screw - Page 2 of 2



em			

No

Fiig:

A003b0

Mil-std (military Standard):

spec.