## NSN 5305-01-630-2308



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-630-2308 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.781 inches **Fastener Length:** Between 4.329 inches and 4.359 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.951 inches and 1.014 inches **Shoulder Diameter:** 0.514 inches and 0.515 inches **Shoulder Length:** 3.365 inches and 3.385 inches first shoulder **Internal Drive Style:** High-torque **End Application:** Kc-135 acft **Thread Diameter:** 0.500 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder Material: Steel comp 4140 or steel comp 4340 or steel comp 8740 **Surface Treatment:** Cadmium and chromate **Thread Series Designator:** Unjf Shelf Life: N/a

**Demilitarization:** No

**Unit Of Measure:** 

## NSN 5305-01-630-2308

Shoulder Screw - Page 2 of 2



Fiig:

A003b0