

View Online at <https://aerobasegroup.com/nsn/5305-01-630-7573>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.324 inches

**Fastener Length:**

0.747 inches

**Head Style:**

Hexagon extended washer

**Head Height:**

0.163 inches

**Width Between Flats:**

0.309 inches

**Extended Washer Diameter:**

0.365 inches

**Extended Washer Thickness:**

0.051 inches

**Internal Drive Style:**

W/o internal drive

**Material Accommodated Thickness:**

Between 0.126 inches and 0.187 inches

**Thread Diameter:**

0.190 inches

**Features Provided:**

Flat washer and lock washer

**Thready Qty Per Inch (tpi):**

32

**Product Name:**

Captive screw, hex hd, low profile, self-locking

**Special Features:**

Floating assembly features two flat washers along with one lockwasher; refer to document ft1080 for additional details

**Material:**

Stainless steel bearing surface of head

**Material Specification:**

Astm a484, 300 series assn standard single material response bearing surface of head

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5059 spec.