## NSN 5305-01-630-7573

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-630-7573

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.324 inches
Fastener Length:
0.747 inches
Head Style:
Hexagon extended washer
Head Height:
0.163 inches
Width Between Flats:
0.309 inches
Extended Washer Diameter:
0.365 inches
Extended Washer Thickness:
0.051 inches
Internal Drive Style:
W/o internal drive
Material Accommodated Thickness:
Between 0.126 inches and 0.187 inches
Thread Diameter:
0.190 inches
Features Provided:
Flat washer and lock washer
Thready Qty Per Inch (tpi):
32
Product Name:
Captive screw, hex hd, low profile, self-locking
Special Features:
Floating assembly features two flat washers along with one lockwasher; refer to document ft1080 for additional details
Material:
Stainless steel bearing surface of head
Material Specification:
Astm a484, 300 series assn standard single material response bearing surface of head
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:

Unf

## NSN 5305-01-630-7573

Panel Screw Assembly - Page 2 of 2



N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0

Mil-std (military Standard):

Mil-s-5059 spec.

Shelf Life: