

View Online at <https://aerobasegroup.com/nsn/5305-01-630-7684>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.420 inches

**Fastener Length:**

Between 1.030 inches and 1.060 inches

**Head Style:**

Flat fillister

**Head Diameter:**

Between 0.365 inches and 0.375 inches

**Head Height:**

0.250 inches

**Extended Washer Diameter:**

Between 0.485 inches and 0.505 inches

**Extended Washer Thickness:**

0.030 inches

**Internal Drive Style:**

Hexagon

**Material Accommodated Thickness:**

0.265 inches

**Thread Diameter:**

0.250 inches

**Width Across Flats:**

0.188 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

5240 pounds per square inch

**Product Name:**

Bolt, captive

**Material:**

Stainless steel washer

**Material Specification:**

Astm-a-313 assn standard single material response sleeve

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5059 spec.