NSN 5305-01-630-7684

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-630-7684

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.420 inches
Fastener Length:
Between 1.030 inches and 1.060 inches
Head Style:
Flat fillister
Head Diameter:
Between 0.365 inches and 0.375 inches
Head Height:
0.250 inches
Extended Washer Diameter:
Between 0.485 inches and 0.505 inches
Extended Washer Thickness:
0.030 inches
Internal Drive Style:
Hexagon
Material Accommodated Thickness:
0.265 inches
Thread Diameter:
0.250 inches
Width Across Flats:
0.188 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
5240 pounds per square inch
Product Name:
Bolt, captive
Material:
Stainless steel washer
Material Specification:
Astm-a-313 assn standard single material response sleeve
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 assn standard single treatment response
Thread Series Designator:

Unjf

NSN 5305-01-630-7684

Panel Screw Assembly - Page 2 of 2



She	lf	Life:	
Oile	••	LIIV.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5059 spec.