NSN 5305-01-631-1758

Machine Screw - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5305-01-631-1758

3a
Thread Direction:
Right-hand
Thread Length:
0.75 inches
Fastener Length:
Between 0.844 inches and 0.875 inches
Head Diameter:
Between 0.740 inches and 0.760 inches
Head Height:
0.125 inches
Internal Drive Style:
Torque set
Thread Diameter:
0.1900 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
Between 28.0 rockwell c and 34.0 rockwell c
Product Name:
Screw, grommet, torq-set 10-32 size
Screw Material:
Steel comp 8740
Bearing Surface Of Head Surface Treatment:
Cadmium
Head Surface Treatment:
Cadmium
Screw Surface Treatment:
Cadmium
Shank Surface Treatment:
Cadmium
Bearing Surface Of Head Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Head Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Screw Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Shank Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response

NSN 5305-01-631-1758

Machine Screw - Page 2 of 2



Sı	ne	ci	al	F	ea	tı	ır	Δ	c	•
9	٧٠	v	u	•	cu	··	•••	·	J	•

Has 1050 or 1020 steel grommet.

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0