NSN 5305-01-640-9268

Setscrew - Page 1 of 2



view Online at https://aerobasegroup.com/hsn/5505-01-640-9266
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
2.100 inches
Fastener Length:
Between 2.120 inches and 2.180 inches
Head Style:
Headless (setscrew)
Point Diameter:
Between 0.270 inches and 0.300 inches
Point Style:
Flat
Internal Drive Style:
Hexagon
End Application:
F-35
Thread Diameter:
0.500 inches
Width Across Flats:
0.250 inches
Thready Qty Per Inch (tpi):
20
Hardness Rating:
33.0 rockwell c and 38.0 rockwell c fastener
Product Name:
Stud, armor mounting
Special Features:
Locking element iaw mil-dtl-18240
Material:
Steel comp 4130 or steel comp 4135 or steel comp 4137 or steel comp 4140 or steel comp 4142 or steel comp 4145 or steel comp 4340
or steel comp 8630 or steel comp 8635 or steel comp 8637 or steel comp 8640 or steel comp 8642 or steel comp 8645 fastener
Material Specification:
Astm a322 assn standard single material response fastener
Surface Treatment:
Zinc fastener
Surface Treatment Specification:
Astm b633, ty ii, sc 2, 0.3 mils thick assn standard single treatment response fastener
Supplementary Features:
Refer to drawing for additional requirements

Unf

Thread Series Designator:

NSN 5305-01-640-9268

Setscrew - Page 2 of 2



Shelf	Life:
N/a	

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-dtl-18240 spec.