NSN 5305-01-642-3586

Machine Screw - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5305-01-642-3586

4g/6g
Thread Direction:
Right-hand
Thread Length:
24.0 millimeters
Fastener Length:
50.0 millimeters
Head Style:
Flat chamfer
Head Diameter:
10.0 millimeters
Head Height:
6.0 millimeters
Single Shear Strength:
4960 pounds per square inch
Internal Drive Style:
Hexagon
Thread Diameter:
6.0 millimeters
Width Across Flats:
5.0 millimeters
Hole Quantity:
Hole Quantity:
•
3
3 Hole Type:
3 Hole Type: Drilled
3 Hole Type: Drilled Min. Tensile Strength (psi):
3 Hole Type: Drilled Min. Tensile Strength (psi): 5870 pounds per square inch
3 Hole Type: Drilled Min. Tensile Strength (psi): 5870 pounds per square inch Hardness Rating:
3 Hole Type: Drilled Min. Tensile Strength (psi): 5870 pounds per square inch Hardness Rating: 38.0 rockwell c and 43.0 rockwell c
Hole Type: Drilled Min. Tensile Strength (psi): 5870 pounds per square inch Hardness Rating: 38.0 rockwell c and 43.0 rockwell c Minimum Yield Strength:
Hole Type: Drilled Min. Tensile Strength (psi): 5870 pounds per square inch Hardness Rating: 38.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 1170 megapascals
Hole Type: Drilled Min. Tensile Strength (psi): 5870 pounds per square inch Hardness Rating: 38.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 1170 megapascals Thread Pitch In Millimeters:
Hole Type: Drilled Min. Tensile Strength (psi): 5870 pounds per square inch Hardness Rating: 38.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 1170 megapascals Thread Pitch In Millimeters: 1.0
Hole Type: Drilled Min. Tensile Strength (psi): 5870 pounds per square inch Hardness Rating: 38.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 1170 megapascals Thread Pitch In Millimeters: 1.0 Hole Configuration Style:
Hole Type: Drilled Min. Tensile Strength (psi): 5870 pounds per square inch Hardness Rating: 38.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 1170 megapascals Thread Pitch In Millimeters: 1.0 Hole Configuration Style: Round
Hole Type: Drilled Min. Tensile Strength (psi): 5870 pounds per square inch Hardness Rating: 38.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 1170 megapascals Thread Pitch In Millimeters: 1.0 Hole Configuration Style: Round Chamfer Angle:
Hole Type: Drilled Min. Tensile Strength (psi): 5870 pounds per square inch Hardness Rating: 38.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 1170 megapascals Thread Pitch In Millimeters: 1.0 Hole Configuration Style: Round Chamfer Angle: 30.0 degrees
Hole Type: Drilled Min. Tensile Strength (psi): 5870 pounds per square inch Hardness Rating: 38.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 1170 megapascals Thread Pitch In Millimeters: 1.0 Hole Configuration Style: Round Chamfer Angle: 30.0 degrees Product Name:
Hole Type: Drilled Min. Tensile Strength (psi): 5870 pounds per square inch Hardness Rating: 38.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 1170 megapascals Thread Pitch In Millimeters: 1.0 Hole Configuration Style: Round Chamfer Angle: 30.0 degrees Product Name: Metric socket head cap screw-alloy steel

NSN 5305-01-642-3586

Machine Screw - Page 2 of 2



Material:
Steel
Material Specification:
Iso4762 international std/spec single material response
Surface Treatment:
Oxide
Thread Series Designator:
M
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A500d0