Assembled Washer Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-642-5907



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.906 inches and 0.937 inches Fastener Length: Between 0.906 inches and 0.937 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.640 inches and 0.660 inches Locking Feature: Lockwasher **Countersink Height:** 0.125 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.1900 inches Thready Qty Per Inch (tpi): 32 Hardness Rating: Between 28.0 rockwell c and 34.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Screw, grommet, offset cross recess 10-32 size **Screw Material:** Steel comp 8740 Locking Feature Material: Steel comp 1050 or steel comp 1020 **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416, type ii, cl 3 assn standard single treatment response **Special Features:** Heat treat gromme (lockwasher) 125 ksi min uts; grommet is at bearing surface of screw head and contours the head; grommet thickness is 0.022/0.028 inches **Thread Series Designator:** Unjf

Shelf Life:

N/a

NSN 5305-01-642-5907

Assembled Washer Screw - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0