NSN 5305-01-642-5909



Assembled Washer Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-642-5909 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.9065 inches and 0.9375 inches **Fastener Length:** Between 0.9065 inches and 0.9375 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.740 inches and 0.760 inches **Locking Feature:** Lockwasher **Countersink Height:** 0.125 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.1900 inches Thready Qty Per Inch (tpi): 32 **Hardness Rating:** Between 28.0 rockwell c and 34.0 rockwell c **Countersink Angle:** 100.0 degrees **Product Name:** Screw, grommet, torq-set 10-32 size **Screw Material:** Steel comp 8740 **Locking Feature Material:** Steel comp 1050 or steel comp 1020 **Screw Surface Treatment:** Cadmium

Screw Surface Treatment Specification:

Qq-p-416, type ii, cl 3 assn standard single treatment response

Special Features:

Heat treat 125 ksi min uts; gromme (lockwasher) is at bearing surface of screw head and contours the head; grommet thickness is 0.022/0.028 inches

Thread Series Designator:

Unjf

Shelf Life:

N/a

NSN 5305-01-642-5909

Assembled Washer Screw - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A003b0