## NSN 5305-01-642-6385



Assembled Washer Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-642-6385 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.719 inches and 0.750 inches **Fastener Length:** Between 0.719 inches and 0.750 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.640 inches and 0.660 inches **Locking Feature:** Lockwasher **Countersink Height:** 0.125 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.1900 inches Thready Qty Per Inch (tpi): 32 **Hardness Rating:** Between 28.0 rockwell c and 34.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Screw, grommet, offset cross recess 10-32 size **Screw Material:** Steel comp 8740 **Locking Feature Material:** Steel comp 1020 or steel comp 1050 **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416, type ii, cl 3 assn standard single treatment response **Special Features:** Heat treat gromme (lockwasher) 125 ksi min uts; grommet is at bearing surface of screw head and contours the head; grommet thickness is 0.022/0.028 inches **Thread Series Designator:** 

N/a

Unjf

Shelf Life:

## NSN 5305-01-642-6385

Assembled Washer Screw - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A003b0