NSN 5305-01-642-9194

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-642-9194 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.438 inches **Fastener Length:** Between 1.611 inches and 1.641 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.429 inches and 0.477 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches Single Shear Strength: 95000 pounds per square inch **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.3125 inches **Grip Length:** Between 1.178 inches and 1.198 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads **Product Name:** Bolt, 100 degree reduced head, phillips recess, close tolerance, a-286, short thread Color: Green threads Material: Iron alloy 660

Material Specification:

Ams5731 or 5737 national standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii, class 2 national standard single treatment response

NSN 5305-01-642-9194

Close Tolerance Screw - Page 2 of 2

A003b0



Thread Series Designator:
Unjc
Specification Data:
80205-nas8702 through 8716 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: