

View Online at <https://aerobasegroup.com/nsn/5305-01-642-9432>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.203 inches

Fastener Length:

0.868 inches

Head Style:

Hexagon

Head Height:

0.136 inches

Width Between Flats:

Between 0.243 inches and 0.251 inches

Internal Drive Style:

Hexagon

Material Accommodated Thickness:

Between 0.020 inches and 0.031 inches

Thread Diameter:

0.138 inches

Width Across Flats:

0.109375 inches

Thready Qty Per Inch (tpi):

32

Product Name:

Captive screw, internal float, high profile, spring-loaded, fixed thread length

Special Features:

Heat treat stu (fastener) to 160 ksi min

Color:

Red bushing

Material:

Stainless steel fastener

Material Specification:

Ams5737 national standard 1st material response fastener

Surface Treatment:

Passivate washer

Surface Treatment Specification:

Mil-a-8625, type ii, class 2 dyed red government std/spec 1st treatment response bushing

Thread Series Designator:

Unc

Specification Data:

0hdw7-s-2374 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5059 spec.