

View Online at <https://aerobasegroup.com/nsn/5305-01-642-9432>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.203 inches

**Fastener Length:**

0.868 inches

**Head Style:**

Hexagon

**Head Height:**

0.136 inches

**Width Between Flats:**

Between 0.243 inches and 0.251 inches

**Internal Drive Style:**

Hexagon

**Material Accommodated Thickness:**

Between 0.020 inches and 0.031 inches

**Thread Diameter:**

0.138 inches

**Width Across Flats:**

0.109375 inches

**Thready Qty Per Inch (tpi):**

32

**Product Name:**

Captive screw, internal float, high profile, spring-loaded, fixed thread length

**Special Features:**

Heat treat stu (fastener) to 160 ksi min

**Color:**

Red bushing

**Material:**

Stainless steel fastener

**Material Specification:**

Ams5737 national standard 1st material response fastener

**Surface Treatment:**

Passivate washer

**Surface Treatment Specification:**

Mil-a-8625, type ii, class 2 dyed red government std/spec 1st treatment response bushing

**Thread Series Designator:**

Unc

**Specification Data:**

0hdw7-s-2374 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5059 spec.