NSN 5305-01-644-4214

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-644-4214 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.750 inches **Fastener Length:** 0.750 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.600 inches and 0.656 inches **Internal Drive Style:** Hexagon **End Application:** 2350-01-577-0830 **Thread Diameter:** 0.312 inches Width Across Flats: 0.188 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 84.0 degrees Material: Steel **Material Specification:** 66 federal standard single material response **Surface Treatment:** Zinc **Surface Treatment Specification:** Astm b633, type ii, class fe/zn 5 assn standard single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

NSN 5305-01-644-4214

Socket Head Cap Screw - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A003b0