

View Online at <https://aerobasegroup.com/nsn/5305-01-645-8395>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.468 inches

**Fastener Length:**

Between 1.891 inches and 1.938 inches

**Head Style:**

Round extended washer

**Head Diameter:**

0.375 inches

**Head Height:**

Between 0.089 inches and 0.099 inches

**Extended Washer Diameter:**

0.437 inches

**Extended Washer Thickness:**

Between 0.025 inches and 0.030 inches

**Spline Major Diameter:**

0.155 inches

**Grip Diameter:**

Between 0.1885 inches and 0.1895 inches

**Internal Drive Style:**

Torx

**Thread Diameter:**

0.1900 inches

**Grip Length:**

Between 1.423 inches and 1.453 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

3185 pounds per square inch

**Product Name:**

Screw, washer head, close tolerance

**Material:**

Stainless steel

**Material Specification:**

Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single material response or ams5853 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Ams-qq-p-35 assn standard single treatment response or ams2700, method 1, class 4 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0