

View Online at <https://aerobasegroup.com/nsn/5305-01-646-9774>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.276 inches

Fastener Length:

Between 0.449 inches and 0.479 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.376 inches and 0.385 inches

Grip Diameter:

Between 0.1885 inches and 0.1895 inches

Shank Unthreaded Hole Diameter:

0.070 inches and 0.080 inches all holes

Internal Drive Style:

Torque-set ribbed

Thread Diameter:

0.1900 inches

Grip Length:

Between 0.178 inches and 0.198 inches

Hole Quantity:

1

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

3180 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Stainless steel

Material Specification:

Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single material response or ams5853 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams-qq-p-416, type ii, class 2 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0