NSN 5305-01-647-1577

Shoulder Screw - Page 1 of 2

Thread Class:

Right-hand

Thread Length:

Thread Direction:

За



View Online at https://aerobasegroup.com/nsn/5305-01-647-1577

Between 0.595 inches and 0.625 inches
Fastener Length:
Between 1.350 inches and 1.370 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.729 inches and 0.750 inches
Head Height:
Between 0.302 inches and 0.312 inches
Shoulder Diameter:
0.4960 inches and 0.4980 inches first shoulder
Shoulder Length:
1.000 inches first shoulder
Internal Drive Style:
Hexagon
Thread Diameter:
0.375 inches
Width Across Flats:
0.250 inches
Thready Qty Per Inch (tpi):
16
Min. Tensile Strength (psi):
9310 pounds per square inch
Hardness Rating:
32.0 rockwell c and 43.0 rockwell c
Shoulder Shape:
Round first shoulder
Product Name:
Screw, shoulder, hexagon
Material:
Aluminum alloy
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416 federal specification single treatment response
Thread Series Designator:
Unc

NSN 5305-01-647-1577

Shoulder Screw - Page 2 of 2



		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0