

View Online at <https://aerobasegroup.com/nsn/5305-01-647-2932>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.2965 inches and 0.3435 inches

**Fastener Length:**

Between 0.2965 inches and 0.3435 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.096 inches and 0.110 inches

**Width Between Flats:**

Between 0.243 inches and 0.251 inches

**Internal Drive Style:**

Cross recess type iii

**Thread Diameter:**

0.1640 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

2170 pounds per square inch

**Product Name:**

Screw, hex head

**Screw Material:**

Stainless steel

**Screw Material Specification:**

Ams5737 assn standard single material response

**Bearing Surface Of Head Surface Treatment:**

Cadmium

**Head Surface Treatment:**

Cadmium

**Screw Surface Treatment:**

Cadmium

**Shank Surface Treatment:**

Cadmium

**Bearing Surface Of Head Surface Treatment Specification:**

Ams-qq-p-416, type ii, class 2 assn standard single treatment response

**Head Surface Treatment Specification:**

Ams-qq-p-416, type ii, class 2 assn standard single treatment response

**Screw Surface Treatment Specification:**

Ams-qq-p-416, type ii, class 2 assn standard single treatment response

**Shank Surface Treatment Specification:**

Ams-qq-p-416, type ii, class 2 assn standard single treatment response

**Thread Series Designator:**

Unjc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0