NSN 5305-01-647-2932

Machine Screw - Page 1 of 2

Thread Class:

За



View Online at https://aerobasegroup.com/nsn/5305-01-647-2932

Thread Direction:
Right-hand
Thread Length:
Between 0.2965 inches and 0.3435 inches
Fastener Length:
Between 0.2965 inches and 0.3435 inches
Head Style:
Dished hexagon
Head Height:
Between 0.096 inches and 0.110 inches
Width Between Flats:
Between 0.243 inches and 0.251 inches
Internal Drive Style:
Cross recess type iii
Thread Diameter:
0.1640 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
2170 pounds per square inch
Product Name:
Screw, hex head
Screw Material:
Stainless steel
Screw Material Specification:
Ams5737 assn standard single material response
Bearing Surface Of Head Surface Treatment:
Cadmium
Head Surface Treatment:
Cadmium
Screw Surface Treatment:
Cadmium
Shank Surface Treatment:
Cadmium
Bearing Surface Of Head Surface Treatment Specification:
Ams-qq-p-416, type ii, class 2 assn standard single treatment response
Head Surface Treatment Specification:
Ams-qq-p-416, type ii, class 2 assn standard single treatment response
Screw Surface Treatment Specification:
Ams-qq-p-416, type ii, class 2 assn standard single treatment response

NSN 5305-01-647-2932

Machine Screw - Page 2 of 2



Shank Surface Ti	reatment S	pecification	:
------------------	------------	--------------	---

Ams-qq-p-416, type ii, class 2 assn standard single treatment response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0