NSN 5305-01-647-7018

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-647-7018

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.453 inches
Fastener Length:
1.703 inches
Head Style:
Flat countersunk
Head Diameter:
0.959 inches
Head Height: 0.215 inches
Grip Diameter:
Between 0.4985 inches and 0.4995 inches
Shank Unthreaded Hole Diameter:
0.106 inches and 0.116 inches all holes
Point Style:
Flat
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.5000 inches
Grip Length:
1.250 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
17460 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Distance From Head Largest Bearing Surface To Shank Hole Center:
1.58 inches all holes
Product Name:
Screw machine-flat 100 degrees head close tolerance short thread offset cruciform 160 ksi
Material:
Iron alloy 660
Material Specification:
Ams5737 assn standard single material response
Surface Treatment:
Passivate

NSN 5305-01-647-7018

Close Tolerance Screw - Page 2 of 2



Surface Treatment Speci

Qq-p-35 type ii or viii federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0