NSN 5305-01-647-9774

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-647-9774

3a         Thread Direction:         Right-hand         Thread Length:         0.276 inches         Fastenr Length:         Between 0.323 inches and 0.353 inches         Head Siyle:         Flat countersunk         Head Dimeter:         0.221 inches         Grip Diameter:         0.221 inches         Point Style:         Flat         Point Style:         Flat         Internal Drive Style:         Flat         Offset cruciform (torque set)         Thread Diameter:         0.1300 inches         Grip Length:         Between 0.052 inches and 0.072 inches         Thread Quy Per Inch (tpi):         32         Min Tensile Strength (psi):         1270 pounds per square inch         Coutersink Angle:         Between 9.0 degrees and 101.0 degrees         Product Name:         Screw machine flat 100 degrees head close tolerance short thread offset cruciform 160 kas         Material Specification:         Nas006 national standard single treatment response         Surface Treatment Specification:         Nas4006 national standard single treatment response         Surface Trea	Thread Class:
Thread Direction:         Right-hand         Thread Length:         0.276 inches         Fastener Length:         0.237 inches         Fastener Length:         Between 0.323 inches and 0.353 inches         Head Style:         Flat countersumk         Head Diameter:         0.221 inches         Grip Diameter:         0.221 inches         Point Style:         Flat         Intread Diameter:         0.1365 inches and 0.1375 inches         Point Style:         Flat         Intread Diameter:         0.1380 inches         Offset cruciform (torque set)         Thread Diameter:         0.1380 inches         Grip Length:         Between 0.052 inches and 0.072 inches         Thready Qty Per Inch (tpi):         32         Min. Tensile Strength (psi):         1270 pounds per square inch         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Product Name:         Screw machine flat 100 degrees head close tolerance short thread offset cruciform 160 kasi         Material         Police Treatment:         Auminum	
Right-hand         Pread Length:         0.276 inches         Fastenr Length:         Between 0.323 inches and 0.353 inches         Head Style:         Flat countersunk         Head Diameter:         0.221 inches         Grip Diameter:         Between 0.1365 inches and 0.1375 inches         Point Style:         Flat         Internal Drive Style:         Offset cruciform (torque set)         Thread Diameter:         0.1380 inches         Grip Length:         1380 inches         Grip Length:         1380 inches         Thread Diameter:         0.1380 inches         1380 inches         Grip Length:         1380 inches         141         Between 0.052 inches and 0.072 inches         170 pounds per square inch         1270 pounds per square inch         1380 field         1400 field Specification: <t< td=""><td></td></t<>	
Particial Length:         0.276 inches         Fastener Length:         Between 0.323 inches and 0.353 inches         Head Style:         Flat countersunk         Head Diameter:         0.221 inches         Grip Diameter:         Between 0.1365 inches and 0.1375 inches         Point Style:         Flat         Internal Drive Style:         Offset cruciform (torque set)         Thread Diameter:         0.1380 inches         Grip Length:         Between 0.052 inches and 0.072 inches         Thready Qty Per Inch (tpi):         1220 pounds per square inch         Coutersink Angle:         Between 9.0 degrees and 10.10 degrees         Product Name:         Screw machine flat 100 degrees head close tolerance short thread offset cruciform 160 kes         Monterial Specification:         Aumizmu         Aums737 assn standard single material response         Surface Treatment Specification:         Aus406 national standard single treatment response         Hurder         Junyf	
0.276 inches         Fastener Length:         Between 0.323 inches and 0.353 inches         Head Style:         Flat countersunk         Head Diameter:         0.221 inches         Grip Diameter:         Between 0.1365 inches and 0.1375 inches         Point Style:         Flat         Interad Drive Style:         Offset cruciform (torque set)         Thread Diameter:         0.1380 inches         Grip Length:         Between 0.052 inches and 0.072 inches         Thread Diameter:         0.1380 inches         Grip Length:         Between 0.052 inches and 0.072 inches         Thready Qty Per Inch (tpi):         32         Min. Tensile Strength (psi):         1270 pounds per square inch         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Portext Mane:         Iron alloy 660         Material Specification:         Ams/573 assn standard single material response         Surface Treatment:         Autonian         Stander Specification:         Ausd06 national standard single treatment response         Thread Series Designator:         Hout	-
Fastener Length:Between 0.323 inches and 0.353 inchesHead Style:Flat countersunkHead Diameter:0.221 inchesBetween 0.1365 inches and 0.1375 inchesPoint Style:FlatInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.1380 inchesGrip Length:Between 0.052 inches and 0.072 inchesThread Yalve Princh (tpi):32Mintersite Strength (psi):1270 pounds per square inchCountersink Angle:Between 9.0 degrees and 101.0 degreesProduct Name:Stread Strength (psi):Batward In Bud Style:1370 pounds per square inchCountersink Angle:In analoy 660Material Specification:AuminumSurface Treatment:AudoG national standard single treatment responseFureda Streis Designator:Nas4006 national standard single treatment responseFureda Streis Designator:Nas4006 national standard single treatment responseFureda Streis Designator:Nas4006 national standard single treatment responseFureda Streis Designator:Hord Streis Designator:Starter Treatment:Starter Treatment: </td <td>-</td>	-
Between 0.323 inches and 0.353 inches         Head Style:         Flat countersunk         Head Diameter:         0.221 inches         Grip Diameter:         Between 0.1365 inches and 0.1375 inches         Point Style:         Flat         Internal Drive Style:         Offset cruciform (torque set)         Thread Diameter:         0.1380 inches         Grip Length:         Between 0.052 inches and 0.072 inches         Thready Qty Per Inch (tpi):         32         Min. Tensile Strength (psi):         1270 pounds per square inch         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Product Name:         Screw machine flat 100 degrees head close tolerance short thread offset cruciform 160 kes         Material Specification:         Ams5737 assn standard single material response         Surface Treatment:         Autinium         Surface Treatment Specification:         Nas4006 national standard single treatment response         Thread Series Designator:         Unif	
Head Style:         Flat countersunk         Head Diameter:         0.221 inches         Grip Diameter:         Between 0.1365 inches and 0.1375 inches         Point Style:         Flat         Internal Drive Style:         Offset cruciform (torque set)         Thread Diameter:         0.1380 inches         Grip Length:         Between 0.052 inches and 0.072 inches         Thready Qty Per Inch (tpi):         32         Min. Tensile Strength (psi):         1270 pounds per square inch         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Product Name:         Screw machine flat 100 degrees head close tolerance short thread offset cruciform 160 ksi         Material:         Iron alloy 660         Material Specification:         Ams5737 assn standard single material response         Surface Treatment:         Aurninum         Surface Treatment Specification:         Nas4006 national standard single treatment response         Thread Series Designator:         Unjf	-
Flat countersunk         Head Diameter:         0.221 inches         Grip Diameter:         Between 0.1365 inches and 0.1375 inches         Point Style:         Flat         Internal Drive Style:         Offset cruciform (torque set)         Thread Diameter:         0.1380 inches         Grip Length:         Between 0.052 inches and 0.072 inches         Thready Qty Per Inch (tpi):         32         Min. Tensile Strength (psi):         1270 pounds per square inch         Countersink Angle:         Between 9.9.0 degrees and 101.0 degrees         Product Name:         Screw machine flat 100 degrees head close tolerance short thread offset cruciform 160 kes         Material:         Iron alloy 660         Material Specification:         Ams5737 assn standard single material response         Surface Treatment:         Autunium         Surface Treatment Specification:         Nas4006 national standard single treatment response         Thread Series Designator:         Unif	
Head Diameter:         0.221 inches         Grip Diameter:         Between 0.1365 inches and 0.1375 inches         Point Style:         Flat         Internal Drive Style:         Offset cruciform (torque set)         Thread Diameter:         0.1380 inches         Grip Length:         Between 0.052 inches and 0.072 inches         Thready Qty Per Inch (tpi):         32         Min. Tensile Strength (psi):         1270 pounds per square inch         Countersink Angle:         Between 9.0 degrees and 101.0 degrees         Product Name:         Screw machine flat 100 degrees head close tolerance short thread offset cruciform 160 ksi         Material:         Iron alloy 660         Material Specification:         Ans5737 assn standard single material response         Surface Treatment:         Auminum         Surface Treatment Specification:         Nas4006 national standard single treatment response         Thread Series Designator:         Unjf	-
0.221 inches 0.221 inches Grip Diameter: Between 0.1365 inches and 0.1375 inches Point Style: Flat Interal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.1380 inches Grip Length: Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 1270 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Product Name: Screw machine flat 100 degrees head close tolerance short thread offset cruciform 160 ksi Material: Iron alloy 660 Material Specification: Ams5737 assn standard single material response Surface Treatment: Aluminum Surface Treatment Specification: Nas4006 national standard single treatment response Thread Series Designator: Unjf Shelf Life:	
Grip Diameter:         Between 0.1365 inches and 0.1375 inches         Point Style:         Flat         Internal Drive Style:         Offset cruciform (torque set)         Thread Diameter:         0.1380 inches         Grip Length:         Between 0.052 inches and 0.072 inches         Thready Qty Per Inch (tpi):         32         Min. Tensile Strength (psi):         1270 pounds per square inch         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Product Name:         Screw machine flat 100 degrees head close tolerance short thread offset cruciform 160 ksi         Material         Iron alloy 660         Material Specification:         Ams5737 assn standard single material response         Surface Treatment:         Aluminum         Surface Treatment Specification:         Nas4006 national standard single treatment response         Thread Series Designator:         Unif         Surface Treatment Specification:         Nas4006 national standard single treatment response         Thread Series Designator:         Unif	
Between 0.1365 inches and 0.1375 inches         Point Style:         Flat         Internal Drive Style:         Offset cruciform (torque set)         Thread Diameter:         0.1380 inches         Grip Length:         Between 0.052 inches and 0.072 inches         Thready Qty Per Inch (tpi):         32         Min. Tensile Strength (psi):         1270 pounds per square inch         Countersink Angle:         Between 9.0.0 degrees and 10.0 degrees         Product Name:         Screw machine flat 100 degrees head close tolerance short thread offset cruciform 160 ksi         Material         Inon alloy 660         Material Specification:         Auminum         Surface Treatment:         Aluminum         Surface Treatment Specification:         Nas4006 national standard single treatment response         Thread Series Designator:         Unif         Surface Treatment Specification:         Nas4006 national standard single treatment response	
Point Style:         Flat         Internal Drive Style:         Offset cruciform (torque set)         Thread Diameter:         0.1380 inches         Grip Length:         Between 0.052 inches and 0.072 inches         Thready Qty Per Inch (tpi):         32         Min. Tensile Strength (psi):         1270 pounds per square inch         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Product Name:         Screw machine flat 100 degrees head close tolerance short thread offset cruciform 160 ksi         Material:         Iron alloy 660         Material Specification:         Arms5737 assn standard single material response         Surface Treatment Specification:         Nas4006 national standard single treatment response         Thread Series Designator:         Unif         Shelf Life:	-
Flat         Internal Drive Style:         Offset cruciform (torque set)         Thread Diameter:         0.1380 inches         Grip Length:         Between 0.052 inches and 0.072 inches         Thready Qty Per Inch (tpi):         32         Min. Tensile Strength (psi):         1270 pounds per square inch         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Product Name:         Screw machine flat 100 degrees head close tolerance short thread offset cruciform 160 ks         Material:         Iron alloy 660         Material         Ams5737 assn standard single material response         Surface Treatment:         Auminum         Surface Treatment Specification:         Nas4006 national standard single treatment response         Thread Series Designator:         Unif         Shef Life:	
Internal Drive Style:         Offset cruciform (torque set)         Thread Diameter:         0.1380 inches         Grip Length:         Between 0.052 inches and 0.072 inches         Thready Qty Per Inch (tpi):         32         Min. Tensile Strength (psi):         1270 pounds per square inch         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Product Name:         Screw machine flat 100 degrees head close tolerance short thread offset cruciform 160 ksi         Material:         Iron alloy 660         Material Specification:         Arms5737 assn standard single material response         Surface Treatment:         Natwinum         Surface Treatment Specification:         Nas4006 national standard single treatment response         Thread Series Designator:         Unif         Sheft Life:	-
Offset cruciform (torque set) <b>Thread Diameter:</b> 0.1380 inches <b>Grip Length:</b> Between 0.052 inches and 0.072 inches <b>Thready Qty Per Inch (tpi):</b> 32 <b>Min. Tensile Strength (psi):</b> 1270 pounds per square inch <b>Countersink Angle:</b> Between 99.0 degrees and 101.0 degreesProduct Name:Screw machine flat 100 degrees head close tolerance short thread offset cruciform 160 ksi <b>Material:</b> Iron alloy 660 <b>Material Specification:</b> Ams5737 assn standard single material response <b>Surface Treatment Specification:</b> Nas4006 national standard single treatment response <b>Thread Series Designator:</b> Unif <b>Shelf Life:</b>	
Thread Diameter:0.1380 inchesGrip Length:Between 0.052 inches and 0.072 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):1270 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesProduct Name:Screw machine flat 100 degrees head close tolerance short thread offset cruciform 160 ksiMaterial:Iron alloy 660Material Specification:Arms5737 assn standard single material responseSurface Treatment:AluminumSurface Treatment Specification:Nas4006 national standard single treatment responseThread Series Designator:UnjfShelf Life:	-
0.1380 inches Grip Length: Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 1270 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Product Name: Screw machine flat 100 degrees head close tolerance short thread offset cruciform 160 ksi Material: Iron alloy 660 Material Specification: Ams5737 assn standard single material response Surface Treatment: Aluminum Surface Treatment Specification: Nas4006 national standard single treatment response Thread Series Designator: Unjf	
Grip Length:Between 0.052 inches and 0.072 inchesFhready Qty Per Inch (tpi):3232Min. Tensile Strength (psi):1270 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesProduct Name:Screw machine flat 100 degrees head close tolerance short thread offset cruciform 160 ksiMaterial:Iron alloy 660Material Specification:Ausf373 assn standard single material responseSurface Treatment:AuminumSurface Treatment Specification:Ins4006 national standard single treatment responseIrread Series Designator:UnjfSurface InterventState InterventState InterventState InterventState InterventSurface Treatment Specification:Surface InterventSurface InterventSurface InterventState InterventSurface InterventSurfa	
Between 0.052 inches and 0.072 inches         Thready Qty Per Inch (tpi):         32         Min. Tensile Strength (psi):         1270 pounds per square inch         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Product Name:         Screw machine flat 100 degrees head close tolerance short thread offset cruciform 160 ksi         Material:         Iron alloy 660         Material Specification:         Ams5737 assn standard single material response         Surface Treatment:         Aluminum         Surface Treatment Specification:         Nas4006 national standard single treatment response         Thread Series Designator:         Unjf         Shelf Life:	
Thready Qty Per Inch (tpi):         32         Min. Tensile Strength (psi):         1270 pounds per square inch         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Product Name:         Screw machine flat 100 degrees head close tolerance short thread offset cruciform 160 ksi         Material:         Iron alloy 660         Material Specification:         Ams5737 assn standard single material response         Surface Treatment:         Aluminum         Surface Treatment Specification:         Nas4006 national standard single treatment response         Thread Series Designator:         Unjf         Shelf Life:	Grip Length:
32 Min. Tensile Strength (psi): 1270 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Product Name: Screw machine flat 100 degrees head close tolerance short thread offset cruciform 160 ksi Material: Iron alloy 660 Material Specification: Ams5737 assn standard single material response Surface Treatment: Aluminum Surface Treatment Specification: Nas4006 national standard single treatment response Thread Series Designator: Unjf	Between 0.052 inches and 0.072 inches
Min. Tensile Strength (psi):1270 pounds per square inch1270 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesProduct Name:Screw machine flat 100 degrees head close tolerance short thread offset cruciform 160 ksiMaterial:Iron alloy 660Material Specification:Ams5737 assn standard single material responseSurface Treatment:AluminumSurface Treatment Specification:Nas4006 national standard single treatment responseThread Series Designator:UnjfShelf Life:	Thready Qty Per Inch (tpi):
1270 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Product Name: Screw machine flat 100 degrees head close tolerance short thread offset cruciform 160 ksi Material: Iron alloy 660 Material Specification: Ams5737 assn standard single material response Surface Treatment: Aluminum Surface Treatment Specification: Nas4006 national standard single treatment response Thread Series Designator: Unjf Shelf Life:	32
Countersink Angle:Between 99.0 degrees and 101.0 degreesProduct Name:Screw machine flat 100 degrees head close tolerance short thread offset cruciform 160 ksiMaterial:Iron alloy 660Material Specification:Ams5737 assn standard single material responseSurface Treatment:AluminumSurface Treatment Specification:Nas4006 national standard single treatment responseThread Series Designator:UnjfShelf Life:	Min. Tensile Strength (psi):
Between 99.0 degrees and 101.0 degrees Product Name: Screw machine flat 100 degrees head close tolerance short thread offset cruciform 160 ksi Material: Iron alloy 660 Material Specification: Ams5737 assn standard single material response Surface Treatment: Aluminum Surface Treatment Specification: Nas4006 national standard single treatment response Thread Series Designator: Unjf Shelf Life:	1270 pounds per square inch
Product Name:Screw machine flat 100 degrees head close tolerance short thread offset cruciform 160 ksiMaterial:Iron alloy 660Material Specification:Ams5737 assn standard single material responseSurface Treatment:AluminumSurface Treatment Specification:Nas4006 national standard single treatment responseThread Series Designator:UnjfShelf Life:	Countersink Angle:
Screw machine flat 100 degrees head close tolerance short thread offset cruciform 160 ksi Material: Iron alloy 660 Material Specification: Ams5737 assn standard single material response Surface Treatment: Aluminum Surface Treatment Specification: Nas4006 national standard single treatment response Thread Series Designator: Unjf Shelf Life:	Between 99.0 degrees and 101.0 degrees
Material:Iron alloy 660Material Specification:Ams5737 assn standard single material responseSurface Treatment:AluminumSurface Treatment Specification:Nas4006 national standard single treatment responseThread Series Designator:UnjfShelf Life:	Product Name:
Iron alloy 660 Material Specification: Ams5737 assn standard single material response Surface Treatment: Aluminum Surface Treatment Specification: Nas4006 national standard single treatment response Thread Series Designator: Unjf Shelf Life:	Screw machine flat 100 degrees head close tolerance short thread offset cruciform 160 ksi
Material Specification:Ams5737 assn standard single material responseSurface Treatment:AluminumSurface Treatment Specification:Nas4006 national standard single treatment responseThread Series Designator:UnjfShelf Life:	Material:
Ams5737 assn standard single material response Surface Treatment: Aluminum Surface Treatment Specification: Nas4006 national standard single treatment response Thread Series Designator: Unjf Shelf Life:	Iron alloy 660
Surface Treatment: Aluminum Surface Treatment Specification: Nas4006 national standard single treatment response Thread Series Designator: Unjf Shelf Life:	Material Specification:
Aluminum Surface Treatment Specification: Nas4006 national standard single treatment response Thread Series Designator: Unjf Shelf Life:	Ams5737 assn standard single material response
Surface Treatment Specification: Nas4006 national standard single treatment response Thread Series Designator: Unjf Shelf Life:	Surface Treatment:
Nas4006 national standard single treatment response Thread Series Designator: Unjf Shelf Life:	Aluminum
Thread Series Designator: Unjf Shelf Life:	Surface Treatment Specification:
Unjf Shelf Life:	Nas4006 national standard single treatment response
Shelf Life:	Thread Series Designator:
	Unjf
N/a	Shelf Life:
N/a	N/a

## NSN 5305-01-647-9774

Close Tolerance Screw - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0