NSN 5305-01-648-4249

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-648-4249

| view Offilite at https://defobasegroup.com/hsh/5505-01-040-4245 |
|---|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.750 inches |
| Fastener Length: |
| 0.750 inches |
| Head Style: |
| Round extended washer |
| Head Diameter: |
| Between 0.302 inches and 0.322 inches |
| Head Height: |
| Between 0.059 inches and 0.064 inches |
| Extended Washer Diameter: |
| Between 0.365 inches and 0.385 inches |
| Extended Washer Thickness: |
| Between 0.023 inches and 0.028 inches |
| Internal Drive Style: |
| Cross recess type iii |
| End Application: |
| Kc-46 tanker |
| Thread Diameter: |
| 0.164 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Screw Material: |
| Titanium alloy |
| Screw Material Specification: |
| Ams4928 assn standard single material response or ams4967 assn standard single material response |
| Screw Surface Treatment: |
| Aluminum and phosphate |
| Screw Surface Treatment Specification: |
| Bbms10-85, type 1, cl a assn standard 1st treatment response and bac5861 assn standard 2nd treatment response |
| Special Features: |
| Faa certified |
| Supplementary Features: |
| K coded part shall be coated with a thermosetting epoxy material applied by stake fastener company, doc 4-04-0525 |
| Thread Series Designator: |
| Unjc |
| Shelf Life: |
| N/a |

NSN 5305-01-648-4249

Machine Screw - Page 2 of 2



| | Of | | | |
|--|----|--|--|--|

--

Demilitarization:

No

Fiig:

A500d0