NSN 5305-01-648-4249

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-648-4249

view Offilite at https://defobasegroup.com/hsh/5505-01-040-4245
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.750 inches
Fastener Length:
0.750 inches
Head Style:
Round extended washer
Head Diameter:
Between 0.302 inches and 0.322 inches
Head Height:
Between 0.059 inches and 0.064 inches
Extended Washer Diameter:
Between 0.365 inches and 0.385 inches
Extended Washer Thickness:
Between 0.023 inches and 0.028 inches
Internal Drive Style:
Cross recess type iii
End Application:
Kc-46 tanker
Thread Diameter:
0.164 inches
Thready Qty Per Inch (tpi):
32
Screw Material:
Titanium alloy
Screw Material Specification:
Ams4928 assn standard single material response or ams4967 assn standard single material response
Screw Surface Treatment:
Aluminum and phosphate
Screw Surface Treatment Specification:
Bbms10-85, type 1, cl a assn standard 1st treatment response and bac5861 assn standard 2nd treatment response
Special Features:
Faa certified
Supplementary Features:
K coded part shall be coated with a thermosetting epoxy material applied by stake fastener company, doc 4-04-0525
Thread Series Designator:
Unjc
Shelf Life:
N/a

NSN 5305-01-648-4249

Machine Screw - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A500d0