## NSN 5305-01-649-3212

Machine Screw - Page 1 of 2

**Shank Surface Treatment Specification:** 



View Online at https://aerobasegroup.com/nsn/5305-01-649-3212

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.5915 inches
Fastener Length:
Between 0.6565 inches and 0.6875 inches
Head Style:
Flat countersunk
Head Diameter:
0.322 inches
Internal Drive Style:
Offset cruciform ribbed
Thread Diameter:
0.1900 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
3180 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Product Name:
Screw machine flat 100 degrees head full thread offset crucif
Screw Material:
Titanium alloy uns r56400
Screw Material Specification:
Ams4957 assn standard single material response
Bearing Surface Of Head Surface Treatment:
Aluminum
Head Surface Treatment:
Aluminum
Screw Surface Treatment:
Aluminum
Shank Surface Treatment:
Aluminum
Head Surface Treatment Specification:
Nas4006 national specification single treatment response or mil-c-83488type11class3 military specification single treatment response
Screw Surface Treatment Specification:
Nas4006 national specification single treatment response or il-c-83488type11class3 military specification 10th treatment response

Nas4006 national specification single treatment response or il-c-83488type11class3 military specification 10th treatment response

## NSN 5305-01-649-3212

Machine Screw - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
<b>Demilitarization:</b> No
No

Mil-std (military Standard): Mil-c-83488type11class3 spec.