## NSN 5305-01-649-5726

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-649-5726 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.500 inches **Fastener Length:** 0.500 inches **Head Style:** Chamfer flange **Head Height:** Between 0.105 inches and 0.120 inches Width Between Flats: Between 0.305 inches and 0.312 inches **Extended Washer Diameter:** Between 0.384 inches and 0.414 inches **Washer Quantity: Internal Drive Style:** Hexagon **End Application:** 6115-01-591-1161 **Thread Diameter:** 0.190 inches Width Across Flats: 0.310 inches **Features Provided:** Lock washer Thready Qty Per Inch (tpi): 32 **Primary Washer Outside Diameter:** Between 0.322 inches and 0.348 inches **Primary Washer Style:** Flat **Primary Washer Material Thickness:** Between 0.019 inches and 0.031 inches **Product Name:** Screw hex with serrated flanged locking head Material: Steel comp 302

**Thread Series Designator:** 

Unf

## NSN 5305-01-649-5726

Assembled Washer Screw - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0