NSN 5305-01-651-3430

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-651-3430

Thread Direction:
Right-hand
Thread Length:
Between 15.7 millimeters and 16.3 millimeters
Fastener Length:
Between 15.7 millimeters and 16.3 millimeters
Head Style:
Hexagon
Head Height:
Between 2.2 millimeters and 2.5 millimeters
Width Between Flats:
Between 6.85 millimeters and 7.00 millimeters
Internal Drive Style:
Torque set
End Application:
1055-01-536-7106
Thread Diameter:
4.0 millimeters
Min. Tensile Strength (psi):
1100 megapascals
Thread Pitch In Millimeters:
0.7
External Thread Tolerance Class:
4h6h
Chamfer Angle:
Between 10.0 degrees and 20.0 degrees
Product Name:
Screw, dual, wrenching, hex head/offset cruciform, a286 cres, full thread, 1100 mpa-metric
Screw Material:
Stainless steel
Screw Material Specification:
Na0026 national specification single material response
Screw Surface Treatment:
Passivate
Screw Surface Treatment Specification:
Qq-p-35 federal standard single treatment response
Bearing Surface Of Head Surface Finish:
0.8 micrometers
Shank Surface Finish:
0.8 micrometers
Thread Surface Finish:

NSN 5305-01-651-3430

Machine Screw - Page 2 of 2

A500d0



Thread Series Designator:
Mj
Specification Data:
80205-na0067 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: