## NSN 5305-01-651-3430

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-651-3430

| Thread Direction:  |
|--|
| Right-hand   |
| Thread Length:   |
| Between 15.7 millimeters and 16.3 millimeters  |
| Fastener Length:   |
| Between 15.7 millimeters and 16.3 millimeters  |
| Head Style:  |
| Hexagon  |
| Head Height:   |
| Between 2.2 millimeters and 2.5 millimeters  |
| Width Between Flats:   |
| Between 6.85 millimeters and 7.00 millimeters  |
| Internal Drive Style:  |
| Torque set   |
| End Application:   |
| 1055-01-536-7106   |
| Thread Diameter:   |
| 4.0 millimeters  |
| Min. Tensile Strength (psi):   |
| 1100 megapascals   |
| Thread Pitch In Millimeters:   |
| 0.7  |
| External Thread Tolerance Class:   |
| 4h6h   |
| Chamfer Angle:   |
| Between 10.0 degrees and 20.0 degrees  |
| Product Name:  |
| Screw, dual, wrenching, hex head/offset cruciform, a286 cres, full thread, 1100 mpa-metric |
| Screw Material:  |
| Stainless steel  |
| Screw Material Specification:  |
| Na0026 national specification single material response                                     |
| Screw Surface Treatment:   |
| Passivate  |
| Screw Surface Treatment Specification:   |
| Qq-p-35 federal standard single treatment response   |
| Bearing Surface Of Head Surface Finish:  |
| 0.8 micrometers  |
| Shank Surface Finish:  |
| 0.8 micrometers  |
| Thread Surface Finish:   |
|  |

## NSN 5305-01-651-3430

Machine Screw - Page 2 of 2

A500d0



| Thread Series Designator:                                 |
|---|
| Mj  |
| Specification Data:                                       |
| 80205-na0067 professional/industrial association standard |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |