

View Online at <https://aerobasegroup.com/nsn/5305-01-651-6350>

**Thread Class:**

4h6h

**Thread Direction:**

Right-hand

**Thread Length:**

Between 13.7 millimeters and 14.3 millimeters

**Fastener Length:**

Between 13.7 millimeters and 14.3 millimeters

**Head Style:**

Hexagon

**Head Height:**

Between 2.7 millimeters and 3.0 millimeters

**Width Between Flats:**

Between 7.85 millimeters and 8.00 millimeters

**Internal Drive Style:**

Torque set

**End Application:**

1055-01-536-7106

**Thread Diameter:**

5.0 millimeters

**Min. Tensile Strength (psi):**

1100 megapascals

**Hardness Rating:**

Between 36.0 rockwell c and 40.0 rockwell c

**Thread Pitch In Millimeters:**

0.8

**Product Name:**

Screw, hex head offset cruciform, alloy steel, full thread, 1100 mpa, metric

**Screw Material:**

Steel comp 4140 or steel comp 4340 or steel comp 8740

**Screw Material Specification:**

Ams6382 national specification 1st material response or ams6415 or ams6484 national specification 2nd material response or ams6322, ams6325 or ams6327 national specification 3rd material response

**Screw Surface Treatment:**

Cadmium

**Screw Surface Treatment Specification:**

Ams-qq-p-416, type ii, class 2 national specification single treatment response

**Thread Series Designator:**

Mj

**Specification Data:**

80205-na0114 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0