

View Online at <https://aerobasegroup.com/nsn/5305-01-651-6350>

Thread Class:

4h6h

Thread Direction:

Right-hand

Thread Length:

Between 13.7 millimeters and 14.3 millimeters

Fastener Length:

Between 13.7 millimeters and 14.3 millimeters

Head Style:

Hexagon

Head Height:

Between 2.7 millimeters and 3.0 millimeters

Width Between Flats:

Between 7.85 millimeters and 8.00 millimeters

Internal Drive Style:

Torque set

End Application:

1055-01-536-7106

Thread Diameter:

5.0 millimeters

Min. Tensile Strength (psi):

1100 megapascals

Hardness Rating:

Between 36.0 rockwell c and 40.0 rockwell c

Thread Pitch In Millimeters:

0.8

Product Name:

Screw, hex head offset cruciform, alloy steel, full thread, 1100 mpa, metric

Screw Material:

Steel comp 4140 or steel comp 4340 or steel comp 8740

Screw Material Specification:

Ams6382 national specification 1st material response or ams6415 or ams6484 national specification 2nd material response or ams6322, ams6325 or ams6327 national specification 3rd material response

Screw Surface Treatment:

Cadmium

Screw Surface Treatment Specification:

Ams-qq-p-416, type ii, class 2 national specification single treatment response

Thread Series Designator:

Mj

Specification Data:

80205-na0114 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0