NSN 5305-01-651-9666



Close Tolerance Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-651-9666 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.406 inches **Fastener Length:** Between 1.453 inches and 1.499 inches **Head Style:** Countersunk cylindrical convex **Grip Diameter:** Between 0.1885 inches and 0.1894 inches **Head Major Diameter:** Between 0.376 inches and 0.385 inches **Internal Drive Style:** Hexagon **End Application:** 1055-01-536-7106 **Thread Diameter:** 0.1900 inches **Grip Length:** 1.062 inches Width Across Flats: Between 0.1260 inches and 0.1290 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** 100.0 degrees Material: Steel comp 4140 or steel comp 4340 or steel comp 8740 **Material Specification:** Ams6382 assn standard single material response or ams6349 assn standard single material response or ams6484 assn standard single material response or ams6414 assn standard single material response or ams6322 assn standard single material response or ams6327 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Ams-qq-p-416, type ii, class 2 assn standard single treatment response **Thread Series Designator:**

Unjf

N/a

Shelf Life:

Unit Of Measure:

NSN 5305-01-651-9666

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0