NSN 5305-01-651-9671

Close Tolerance Screw - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5305-01-651-9671 |
|--|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.406 inches |
| Fastener Length: |
| Between 0.891 inches and 0.937 inches |
| Head Style: |
| Countersunk cylindrical convex |
| Grip Diameter: |
| Between 0.1885 inches and 0.1894 inches |
| Head Major Diameter: |
| Between 0.376 inches and 0.385 inches |
| nternal Drive Style: |
| Hexagon |
| End Application: |
| 1055-01-536-7106 |
| Thread Diameter: |
| 0.1900 inches |
| Grip Length: |
| 0.500 inches |
| Width Across Flats: |
| Between 0.1260 inches and 0.1290 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Countersink Angle: |
| 100.0 degrees |
| Material: |
| Steel comp 4140 or steel comp 4340 or steel comp 8740 |
| Material Specification: |
| Ams6382 assn standard single material response or ams6349 assn standard single material response or ams6484 assn standard single |
| material response or ams6414 assn standard single material response or ams6322 assn standard single material response or ams6327 |
| assn standard single material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Ams-qq-p-416, type ii, class 2 assn standard single treatment response |
| Thread Series Designator: |
| |
| Shelf Life: |
| N/a |
| Material: Steel comp 4140 or steel comp 4340 or steel comp 8740 Material Specification: Ams6382 assn standard single material response or ams6349 assn standard single material response or ams6484 assn standard single material response or ams6414 assn standard single material response or ams6327 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Ams-qq-p-416, type ii, class 2 assn standard single treatment response Thread Series Designator: Unjf Shelf Life: |

Unit Of Measure:

NSN 5305-01-651-9671

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0