NSN 5305-01-651-9698



Close Tolerance Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-651-9698 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.531 inches **Fastener Length:** Between 1.704 inches and 1.750 inches **Head Style:** Countersunk cylindrical convex **Grip Diameter:** Between 0.3108 inches and 0.3117 inches **Head Major Diameter:** Between 0.625 inches and 0.635 inches **Internal Drive Style:** Hexagon **End Application:** 1055-01-536-7106 **Thread Diameter:** 0.3125 inches **Grip Length:** 1.188 inches Width Across Flats: Between 0.1885 inches and 0.1905 inches Thready Qty Per Inch (tpi): 24 **Countersink Angle:** 100.0 degrees Material: Steel comp 4140 or steel comp 4340 or steel comp 8740 **Material Specification:** Ams6382 assn standard single material response or ams6349 assn standard single material response or ams6484 assn standard single material response or ams6414 assn standard single material response or ams6322 assn standard single material response or ams6327 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Ams-qq-p-416, type ii, class 2 assn standard single treatment response **Thread Series Designator:**

Unjf

N/a

Shelf Life:

Unit Of Measure:

NSN 5305-01-651-9698

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0