

View Online at <https://aerobasegroup.com/nsn/5305-01-651-9698>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.531 inches

Fastener Length:

Between 1.704 inches and 1.750 inches

Head Style:

Countersunk cylindrical convex

Grip Diameter:

Between 0.3108 inches and 0.3117 inches

Head Major Diameter:

Between 0.625 inches and 0.635 inches

Internal Drive Style:

Hexagon

End Application:

1055-01-536-7106

Thread Diameter:

0.3125 inches

Grip Length:

1.188 inches

Width Across Flats:

Between 0.1885 inches and 0.1905 inches

Thready Qty Per Inch (tpi):

24

Countersink Angle:

100.0 degrees

Material:

Steel comp 4140 or steel comp 4340 or steel comp 8740

Material Specification:

Ams6382 assn standard single material response or ams6349 assn standard single material response or ams6484 assn standard single material response or ams6414 assn standard single material response or ams6322 assn standard single material response or ams6327 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams-qq-p-416, type ii, class 2 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0