

View Online at <https://aerobasegroup.com/nsn/5305-01-653-9550>

**Thread Class:**

4h6h

**Thread Direction:**

Right-hand

**Thread Length:**

Between 11.7 millimeters and 12.3 millimeters

**Fastener Length:**

Between 11.7 millimeters and 12.3 millimeters

**Head Style:**

Hexagon

**Head Height:**

Between 2.7 millimeters and 3.0 millimeters

**Width Between Flats:**

Between 7.85 millimeters and 8.00 millimeters

**Internal Drive Style:**

Offset cruciform ribbed

**End Application:**

1055-01-536-7106

**Thread Diameter:**

5.0 millimeters

**Min. Tensile Strength (psi):**

13900 newtons per square millimeter

**Hardness Rating:**

Between 36.0 rockwell c and 40.0 rockwell c

**Thread Pitch In Millimeters:**

0.8

**Product Name:**

Screw, dual wrenching, hex head/offset cruciform, a286 cres, full thread, 1100 mpa, metric

**Screw Material:**

Iron alloy 660

**Screw Material Specification:**

Ams5731, ams5732, ams5737 or ams5853, a286 per na0067 national specification single material response

**Screw Surface Treatment:**

Passivate

**Screw Surface Treatment Specification:**

Ams2700, method 1, class 4 national specification single treatment response

**Thread Series Designator:**

Mj

**Specification Data:**

80205-na0067 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0