

View Online at <https://aerobasegroup.com/nsn/5305-01-653-9550>

Thread Class:

4h6h

Thread Direction:

Right-hand

Thread Length:

Between 11.7 millimeters and 12.3 millimeters

Fastener Length:

Between 11.7 millimeters and 12.3 millimeters

Head Style:

Hexagon

Head Height:

Between 2.7 millimeters and 3.0 millimeters

Width Between Flats:

Between 7.85 millimeters and 8.00 millimeters

Internal Drive Style:

Offset cruciform ribbed

End Application:

1055-01-536-7106

Thread Diameter:

5.0 millimeters

Min. Tensile Strength (psi):

13900 newtons per square millimeter

Hardness Rating:

Between 36.0 rockwell c and 40.0 rockwell c

Thread Pitch In Millimeters:

0.8

Product Name:

Screw, dual wrenching, hex head/offset cruciform, a286 cres, full thread, 1100 mpa, metric

Screw Material:

Iron alloy 660

Screw Material Specification:

Ams5731, ams5732, ams5737 or ams5853, a286 per na0067 national specification single material response

Screw Surface Treatment:

Passivate

Screw Surface Treatment Specification:

Ams2700, method 1, class 4 national specification single treatment response

Thread Series Designator:

Mj

Specification Data:

80205-na0067 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A500d0