

View Online at <https://aerobasegroup.com/nsn/5305-01-653-9873>

Thread Class:

4h6h

Thread Direction:

Right-hand

Thread Length:

Between 29.7 millimeters and 30.3 millimeters

Fastener Length:

Between 29.7 millimeters and 30.3 millimeters

Head Style:

Hexagon

Head Height:

Between 3.2 millimeters and 3.5 millimeters

Width Between Flats:

Between 9.78 millimeters and 10.00 millimeters

Internal Drive Style:

Offset cruciform ribbed

End Application:

1055-01-536-7106

Thread Diameter:

6.0 millimeters

Min. Tensile Strength (psi):

19800 newtons per square millimeter

Hardness Rating:

Between 36.0 rockwell c and 40.0 rockwell c

Thread Pitch In Millimeters:

1.0

Product Name:

Screw, hex head, offset cruciform, alloy steel, full thread, 1100 mpa, metric

Screw Material:

Steel comp 4140 or steel comp 4340 or steel comp 8740

Screw Material Specification:

Ams6382 national specification 1st material response or ams6415 national specification 2nd material response or ams6484 national specification 3rd material response or ams6322 national specification 4th material response or ams6325 national specification 5th material response or ams6327 national specification 6th material response

Screw Surface Treatment:

Cadmium

Screw Surface Treatment Specification:

Ams-qq-+416, type ii, class 2 (8-14 um thick) national specification single treatment response

Bearing Surface Of Head Surface Finish:

0.8 micrometers

Shank Surface Finish:

0.8 micrometers

Thread Surface Finish:

0.8 micrometers

Thread Series Designator:

Mj

Specification Data:

80205-na0114 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0