NSN 5305-01-654-4880

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-654-4880 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.425 inches **Fastener Length:** Between 1.473 inches and 1.503 inches **Head Style:** Flat countersunk **Head Diameter:** 0.461 inches **Internal Drive Style:** High-torque **End Application:** Missile **Thread Diameter:** 0.2500 inches Thready Qty Per Inch (tpi): 28 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 4140 or steel comp 4340 or steel comp 8740 **Screw Material Specification:** Ams6382 assn standard 1st material response or ams6415 assn standard 2nd material response or ams6484 assn standard 2nd material response or ams6322 assn standard 3rd material response or ams6325 assn standard 3rd material response or ams6327 assn standard 3rd material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Ams-qq-p-416, type ii, class 2 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

Fiig:

A500d0