

View Online at <https://aerobasegroup.com/nsn/5305-01-654-4932>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.610 inches

Fastener Length:

Between 0.718 inches and 0.750 inches

Head Style:

Pan

Head Diameter:

Between 0.357 inches and 0.373 inches

Head Height:

Between 0.122 inches and 0.132 inches

Washer Quantity:

2

Internal Drive Style:

Cross recess type ii

End Application:

B-52

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Secondary Washer Relationship To Primary Washer:

Not identical

Secondary Washer Style:

Split helical ring

Primary Washer Outside Diameter:

Between 0.338 inches and 0.348 inches

Secondary Washer Outside Diameter:

0.337 inches

Primary Washer Style:

Flat

Primary Washer Material Thickness:

Between 0.029 inches and 0.035 inches

Product Name:

Screw, pan head, assembled washers

Material:

Steel comp 302 or steel comp 304 fastener

Material Specification:

Ams5516, ams5903, ams5904, ams5905 or ams5906 assn standard 1st material response or ams5513, ams5910, ams5911, ams5912, or ams5913 assn standard 2nd material response or astm a 493 assn standard 3rd material response primary washer

Surface Treatment:

Passivate

Surface Treatment Specification:

Ams2700, method 1, class 4 national standard single treatment response

Thread Series Designator:

Unf

Specification Data:

80205-nas1301 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0