

View Online at <https://aerobasegroup.com/nsn/5305-01-654-4932>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.610 inches

**Fastener Length:**

Between 0.718 inches and 0.750 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.357 inches and 0.373 inches

**Head Height:**

Between 0.122 inches and 0.132 inches

**Washer Quantity:**

2

**Internal Drive Style:**

Cross recess type ii

**End Application:**

B-52

**Thread Diameter:**

0.190 inches

**Thread Qty Per Inch (tpi):**

32

**Secondary Washer Relationship To Primary Washer:**

Not identical

**Secondary Washer Style:**

Split helical ring

**Primary Washer Outside Diameter:**

Between 0.338 inches and 0.348 inches

**Secondary Washer Outside Diameter:**

0.337 inches

**Primary Washer Style:**

Flat

**Primary Washer Material Thickness:**

Between 0.029 inches and 0.035 inches

**Product Name:**

Screw, pan head, assembled washers

**Material:**

Steel comp 302 or steel comp 304 fastener

**Material Specification:**

Ams5516, ams5903, ams5904, ams5905 or ams5906 assn standard 1st material response or ams5513, ams5910, ams5911, ams5912, or ams5913 assn standard 2nd material response or astm a 493 assn standard 3rd material response primary washer

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Ams2700, method 1, class 4 national standard single treatment response

**Thread Series Designator:**

Unf

**Specification Data:**

80205-nas1301 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0