## NSN 5305-01-655-5159



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-655-5159 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.420 inches **Fastener Length:** Between 0.497 inches and 0.500 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.371 inches and 0.385 inches **Head Height:** 0.080 inches **Internal Drive Style:** High-torque **End Application:** Missile **Thread Diameter:** 0.1900 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Screw, machine, self-locking **Screw Material:** Stainless steel **Screw Material Specification:** Ams 5732 assn standard single material response or ams 5737 assn standard single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Ams-qq-p-35, type ii or viii, and apply kal-gard 7200f, color flat black assn standard single treatment response

**Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

## NSN 5305-01-655-5159

Machine Screw - Page 2 of 2



Fiig:

A500d0