Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-657-1835

| Thread Class:                                    |
|--|
| 3a   |
| Thread Direction:                                |
| Right-hand                                       |
| Thread Length:                                   |
| 0.516 inches                                     |
|  |
| Fastener Length:<br>0.750 inches                 |
|  |
| Head Style:<br>Flat countersunk undercut         |
| Head Diameter:                                   |
| Between 0.720 inches and 0.781 inches            |
|  |
| Head Height:<br>0.234 inches                     |
|  |
| Internal Drive Style:                            |
| Hexagon  |
| End Application:                                 |
| Mrap - m-atv ui w/ogpk<br>Thread Diameter:       |
| 0.375 inches                                     |
| Width Across Flats:                              |
|  |
| 0.219 inches                                     |
| Thready Qty Per Inch (tpi):                      |
|  |
| Countersink Angle:                               |
| 82.0 degrees                                     |
| Product Name:                                    |
| Screw, flat, socket .38 - 16 tab is mb           |
| Color:   |
| Black  |
| Material:  |
| Steel  |
| Material Specification:                          |
| Astm f835 assn standard single material response |
| Surface Treatment:                               |
| Phosphate zinc                                   |
| Thread Series Designator:                        |
| Unc  |
| Shelf Life:                                      |
| N/a  |
| Unit Of Measure:                                 |
|  |

## NSN 5305-01-657-1835

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

