## NSN 5305-01-657-3702

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-657-3702 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.276 inches **Fastener Length:** 1.151 inches **Head Style:** Fillister **Head Diameter:** Between 0.255 inches and 0.270 inches **Head Height:** Between 0.088 inches and 0.102 inches **Grip Diameter:** Between 0.1625 inches and 0.1635 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.1640 inches **Grip Length:** Between 0.865 inches and 0.885 inches Thready Qty Per Inch (tpi): 32 Material: Steel comp 4140 or steel comp 4340 or steel comp 8740 **Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Sae-ams-qq-p-416 international std/spec single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1122 national std/spec Shelf Life: N/a

No

**Unit Of Measure:** 

Demilitarization:

## NSN 5305-01-657-3702

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.